



ELECTRICAL

1. CURRENT RATING: 1.5AMPS@25° C
2. VOLTAGE RATING: 125V AC
3. INSULATION RESISTANCE: 1000MΩ MIN. @500VDC
4. WITHSTANDING VOLTAGE: 1000V AC RMS OR1500V DC
@ 0.5mA 50Hz or 60Hz 1Minute
5. CONTACT RESISTANCE: $\geq 30\text{m}\Omega$ Max

WORKING TEMPERATURE: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

MECHANICAL


- 1.MATING FORCE: 30N Max
- 2.RETENTION STRENGTH: ≥ 76 N
- 3.DURABILITY: ≥ 750 CYCLES MIN

MATERIAL

1. HOUSING: PA FILLED WITH FIBERGLASS
2. INSERT MATERIAL: PA FILLED WITH FIBERGLASS
3. CONTACT MATERIAL: PHOSPHOR BRONZE $\phi 0.46\text{mm}$
4. CONTACT PLATING: 3 μ "INCH, 6 μ "INCH, 15 μ "INCH, 30 μ "INCH, 50 μ "INCH

受控文件

PC Board Layout



DESIGN	MISS ZENG	SC ALL			未注公差 T00LERANCE		品名： 网口连接器
DRAWIGN	MISS LI	ANIT	MM		.0 ±0.20	ANGLES ±5°	
CHECK	Mr. ZENG	SIZE	A4：210*297		.00 ±0.15		
APPROVAL		VERSION	01		.000 ±0.1		
							型号： HHRJ45-5618-10p8c



东莞市航宏电子科技有限公司
Dongguan Hanghong Electronics Co., Ltd.