





PC Board Layout



SPECIFICATIONS

ELECTRICAL

1. CURRENT RATING: 1.5AMPS@25° C
2. VOLTAGE RATING: 125V AC
3. INSULATION RESISTANCE: 1000MΩ MIN. @500VDC
4. WITHSTANDING VOLTAGE: 1000V AC RMS OR 1500V DC @ 0.5mA 50Hz or 60Hz 1Minute
5. CONTACT RESISTANCE: $\geq 30m\Omega$ Max

WORKING TEMPERATURE: -40°C ~ +85°C

MECHANICAL

1. MATING FORCE: 30N Max
2. RETENTION STRENGTH: $\geq 76N$
3. DURABILITY: ≥ 750 CYCLES MIN

MATERIAL

1. HOUSING: PA FILLED WITH FIBERGLASS
2. INSERT MATERIAL: PA FILLED WITH FIBERGLASS
3. CONTACT MATERIAL: PHOSPHOR BRONZE Ø0.46mm
4. CONTACT PLATING: $\geq 3\mu$ INCH, 3 μ INCH, 6 μ INCH, 15 μ INCH, 30 μ INCH, 50 μ INCH

受控文件

DESIGN	MISS ZENG	SC ALL			未注公差 T00LERANCE		品名：
DRAWIGN	MISS LI	ANIT	MM		.0 ±0.20	ANGLES ±5°	网口连接器
CHECK	Mr. ZENG	SIZE	A4 : 210*297		.00 ±0.15		型号：
APPROVAL		VERSION	01		.000 ±0.1		HHRJ45-5916-8p8c



东莞市航宏电子科技有限公司
Dongguan Hanghong Electronics Co., Ltd.